

Grounding / Insulators

Lay-In Grounding Lugs

Aluminum

	Ground Wire Size	
AL4	4 - 14	100
AL1/0	1/0 - 8	100
AL3/0	3/0 - 6	50
AL250	250mcm - 6	50

Copper

	Ground Wire Size	
CL4	4 - 14	100
CL1/0	1/0 - 8	100
CL3/0	3/0 - 6	50
CL250	250mcm - 6	50



Water Pipe Ground Clamps

Zinc Die Cast with Steel Screws

	Trade Size	Ground Wire Size		
		MIN	MAX	
10BG	1/2" - 1"	8 SOL.	2 STR.	25

Bronze with Bronze Screws for Direct Burial

	Trade Size	Ground Wire Size		
		MIN	MAX	
10BR	1/2" - 1"	10 SOL.	2 STR.	25



Bronze with Steel Screws

	Trade Size	Ground Wire Size		
		MIN	MAX	
10B	1/2" - 1"	10 SOL.	2 STR.	25
34B	1-1/4" - 2"	10 SOL.	2 STR.	1
35A	2-1/2" - 4"	10 SOL.	2 STR.	1
36A	4" - 6"	10 SOL.	2 STR.	1



Ground Rod Clamps - Listed for Direct Burial

	Trade Size	
200	1/2"	100
201	5/8"	100
202	3/4"	100



Copper Alloy with Bronze Bolt

Standoff Insulators

	Size	Suggested Indoor Voltage Rating	
559600 (black)	1" High - 1/4" x 20 Thread	600	1
559620 (black)	1-1/4" High - 1/4" x 20 Thread	600	1
559660 (black)	1-1/2" High - 3/8" x 16 Thread	1500	1
559670 (black)	1-3/4" High - 3/8" x 16 Thread	2000	1
559680 (black)	2" High - 3/8" x 16 Thread	2300	1
559681 (black)	2" High - 1/2" x 13 Thread	2300	1



Other Sizes Available