

# Retractable Cords

## TPR POWER CORDS

Catalog Number	Retracted Length	Number of Conductors	Type	Maximum Voltage	Temperature (°C)	Cable OD (inches)
<b>18 AWG</b>						
72180	12, 24, 36, 48	2	SVEO/SVTO	300	105°	.242
72181	12, 24, 36, 48	2	SJEOW/SJT	300	105°	.300
73181	12, 24, 36, 48	3	SJEOW/SJT	300	105°	.308
74181	12, 24, 36, 48	4	SJEOW/SJT	300	105°	.340
75181	12, 24, 36, 48	5	SJEOW/SJT	300	105°	.385
77182	12, 24, 36, 48	7	SEOW/STO	600	105°	.500
710182	12, 24, 36, 48	10	SEOW/STO	600	105°	.590
<b>16 AWG</b>						
73161	12, 24, 36, 48	3	SJEOW/SJT	300	105°	.340
74161	12, 24, 36, 48	4	SJEOW/SJT	300	105°	.365
74162	12, 24, 36, 48	4	SEOW/STO	600	105°	.425
76162	12, 24, 36, 48	6	SEOW/STO	600	105°	.530
78162	12, 24, 36, 48	8	SEOW/STO	600	105°	.570
<b>14 AWG</b>						
73142	12, 24, 36, 48	3	SEOW/STO	600	105°	.540
74142	12, 24, 36, 48	4	SEOW/STO	600	105°	.570
<b>12 AWG</b>						
73122	12, 24, 36, 48	3	SEOW/STO	600	105°	.580
74122	12, 24, 36, 48	4	SEOW/STO	600	105°	.660

Soft, Bare Copper, TPR Insulated

TPR, Black Jacket

## PVC POWER CORDS

Catalog Number	Retracted Length	Number of Conductors	Type	Maximum Voltage	Temperature (°C)	Cable OD (inches)
<b>18 AWG</b>						
92180	12, 24, 36, 48	2	SVT	300	105°	.250
93180	12, 24, 36, 48	3	SVT	300	105°	.260
92181	12, 24, 26, 48	2	SJT	300	105°	.295
93181	12, 24, 36, 48	3	SJT	300	105°	.330
94181	12, 24, 36, 48	4	SJT	300	105°	.360
95181	12, 24, 36, 48	5	SJT	300	105°	.440
<b>16 AWG</b>						
92161	12, 24, 36, 48	2	SJT	300	105°	.315
93161	12, 24, 36, 48	3	SJT	300	105°	.355
94161	12, 24, 36, 48	4	SJT	300	105°	.410
<b>14 AWG</b>						
93141	12, 24, 36, 48	3	SJT	300	105°	.390
<b>12 AWG</b>						
93121	12, 24, 36, 48	3	SJT	300	105°	.435

Soft, Bare Copper, PVC Insulated

PVC, Black Jacket (available)

LENGTH CHART (1:5 Extension Ratio)		
Retracted Length	Extended Length	Tangent Length Both Ends
12 inches	5 feet	12 inches
24 inches	10 feet	6 inches
36 inches	15 feet	6 inches
48 inches	20 feet	6 inches



Many Other Cords Available. Please Call.